

## Specifications

Construction: High Density  
Fiberboard

Edge Type: Beveled

Thickness: 12.3mm

Length: 48"

Width: 5"

Coverage per Carton: 19.62 ft<sup>2</sup>

Pieces per Carton: 12

Weight per Carton: 39 lbs.

Installation Method: Floating

Recommended Usage: Residential

Underlayment Required: Yes



This product is protected by a 25  
year residential warranty



Abrasion Class 3 Rating works well in  
all areas of the home and can  
withstand normal household traffic




This floor is compliant with Phase 2  
emissions standards of the  
California Air Resources Board.

This collection provides a unique variety of styles and colors making it  
one of our most popular lines.

## Features

- ☒ *UV Resistant*
- ☒ *Fire Resistant*
- ☒ *Scratch Resistant*
- ☒ *Slip Resistant*
- ☒ *Stain Resistant*
- ☒ *Fade Resistant*
- ☒ *Hypoallergenic*
- ☒ *Non Toxic*
- ☒ *Mildew Resistant*
- ☒ *Easy Maintenance*


## Recommended Underlayment



2mm or  
3mm Blue




2mm or  
3mm Silver



EVA



XPE



Felt



Rubber



¼ Cork



½ Cork

## Accessories

### MATCHING MOLDINGS AVAILABLE



Flush Stair Nosing



Stair Nosing



Quarter Round



Reducer



End Cap



T-Molding