

Specifications

Construction: Rigid Core LVT

Edge Type: Beveled

Overall Thickness: 4mm

Wear Layer: 0.5mm (20mil)

Length: 60"

Width: 9"

Coverage per Carton: 22.12 ft²

Pieces per Carton: 6

Weight per Carton: 37 lbs.

Installation Method: Floating

Recommended Usage: Residential & Light Commercial

Underlayment Recommended: Yes



This product is protected by a 25 year residential/5 year light commercial warranty



This floor is waterproof and won't be affected by household spills

Features

These luxury vinyl floors are constructed with a high density thermo- plastic composite which is extremely stable and can be installed over most subfloors. Since there are no wood fibers, these floors are 100% waterproof and can be wet mopped. The 5ft planks and natural embossing allow for an authentic wood look while the rigid core resists indentations and wear from everyday household traffic.


Recommended Underlayment

- **WPCEVA** 1mm Black EVA Foam with 0.1mm black PE film
- **WPCSS** 1.5mm high density black foam with 0.1mm black PE film
- **WPCZS** 1.5mm Zero Slip foam

Certifications

 <p>GREENGUARD PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS UL.COM/GG UL-2818</p>	<p>GREENGUARD Certification ensures that a product has met some of the world's most rigorous and comprehensive standards for low emissions of volatile organic compounds (VOCs) into indoor air.</p>
 <p>floor score CERTIFIED BY SCS Global Services</p>	<p>FloorScore® is the most recognized indoor air quality (IAQ) certification standard for hard surface flooring materials, adhesives, and underlayments.</p>

Accessories



Product	Overall Thickness	4mm (No Pad)
Dimensions	Width and Length	225mm W x 1522mmL
Packaging (Per Carton)	6 Planks	22.12 Sq.Ft. 37 Lbs
Construction	Top Layers	High Definition Decor Film
		Enhanced Polyurethane Coating
		20 Mil Wear Layer
	Core	3.7mm Limestone Composite: min. 64% stone, 0% wood, 100% Virgin Material
	Density	1900kg/m ³ ±10%
	Pad	No pad
	Bevel	beveled
Installation	Floating Glueless	
Under Floor Heating	Approved - See installation manual for details.	
Warranty	25 years Residential/5 Years Light Commercial	
Test Data		
Static Load	ASTM F970	2000PSI
Heat Exposure Resistance F1700	ASTM F2199 EN16511	0.05% Class 34, Heavy Commercial
Swelling after submersion	NALFA LF 01-2011	0% Class 4, Heavy Commercial
IIC & STC	ASTM E492 & ASTM E90	IIC= 56 / STC= 61 with 1.5mm pad: IIC=65 / STC=61
Castor Chair	ISO 4918	Pass
Fire Rating	ASTM E648/ 662	Class I
Wear Resistance	EN 13329 method A	Class 33, Heavy Commercial
Residual Indentation F1700	ASTM F1914 EN 16511	0.5% Class 34, Heavy Commercial
Impact Resistance (Big Ball)	NALFA LF01-2011 EN 16511	Class 4, Heavy Commercial IC3, Class 34, Heavy Commercial
Impact Resistance (Small Ball)	NALFA LF01-2011 EN 16511	Class 4, Heavy Commercial IC3, Class 34, Heavy Commercial
Static coefficient of Friction	ASTM D2047	Dry: 0.38, Wet: 0.9
Resistance to staining F1700	ASTM F925 NALFA LF01-2011	Pass Class 4, Heavy Commercial
Chemical Composition		
VOC	FloorScore™	Pass
Ortho-phthalates	Prop 65	Not Detected / In Compliance
Lead	CPSIA	None Detected
Substances of Very High Concern (SVHC) (Mercury, Chromium VI, Cadmium, SCCp, Benzene, Xylene, Tributyltin, etc.)	Not Detected	